

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
4 May 2006 (04.05.2006)

PCT

(10) International Publication Number  
**WO 2006/046723 A1**

- (51) **International Patent Classification:**  
*G06N 5/04* (2006.01) *A61B 5/16* (2006.01)
- (21) **International Application Number:**  
PCT/JP2005/019941
- (22) **International Filing Date:** 25 October 2005 (25.10.2005)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**  
2004-312858 27 October 2004 (27.10.2004) JP
- (71) **Applicant (for all designated States except US):** CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).
- (72) **Inventors; and**
- (75) **Inventors/Applicants (for US only):** ISHII, Mie [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). MATSUGU, Masakazu [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).

MORI, Katsuhiko [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP). MITARAI, Yusuke [JP/JP]; c/o CANON KABUSHIKI KAISHA, 3-30-2, Shimomaruko, Ohta-ku, Tokyo 1468501 (JP).


(74) **Agent:** OHTSUKA, Yasunori; 7th FL., SHUWA KIOI-CHO PARK BLDG., 3-6, KIOICHO, CHIYODA-KU, Tokyo 1020094 (JP).

(81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH,

[Continued on next page]

(54) **Title:** ESTIMATION APPARATUS AND ITS CONTROL METHOD



(57) **Abstract:** ABSTRACT A condition analysis unit (1302) estimates a surrounding environment and psychological state of the user on the basis of image data, voice data, and living body information. When the estimated psychological state is a predetermined state, a cause estimation unit (1303) estimates based on the living body information whether or not the physical condition of the user is bad. When the estimated psychological state is the predetermined state, the cause estimation unit estimates a cause of the psychological state on the basis of the surrounding environment.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

## DESCRIPTION

## ESTIMATION APPARATUS AND ITS CONTROL METHOD

## TECHNICAL FIELD

5           The present invention relates to a technique for estimating information that pertains to an emotion of the user.

## BACKGROUND ART

10           Conventionally, it is demanded to realize an interface apparatus which recognizes the personality and emotion of a person and executes processing in accordance with the recognition result. In order to implement such human processing, it is indispensable to  
15   develop a personality recognition technique and emotion recognition technique required to recognize the personality and emotion of the user.

          According to the conventional technique associated with emotion recognition, emotion  
20   recognition is made on the basis of voice information and image information (such as an expression, action, or the like) of the user (for example, Japanese Patent Laid-Open Nos. 5-12023, 10-228295, and 2001-83984). In patent reference 2 of them, an emotion recognition  
25   result obtained based on voice information and that obtained from image (expression) information are

multiplied by predetermined weights and are combined,  
thus obtaining a final emotion recognition result.

In Japanese Patent Laid-Open No. 2001-83984, the  
personality is recognized in consideration of physical  
5 and action features of the user in addition to the  
voice and expression information, thus further  
improving the emotion recognition precision.

By the way, human emotions such as delight, anger,  
sorrow, and pleasure necessarily have causes that drive  
10 such emotions. For example, when a person is "angry",  
this emotion may have various causes.

The conventional interface apparatus applies the  
same control to the same emotion independently of the  
psychological state and physical condition of the user.

15 The present invention has been made in  
consideration of the above problems, and has as its  
object to provide a technique which estimates a cause  
that has driven the user to the current emotion, and  
communicates with the user in accordance with the  
20 estimated cause.

#### DISCLOSURE OF INVENTION

In order to achieve an object of the present  
invention, for example, an estimation apparatus of the  
25 present invention comprises the following arrangement.

That is, an estimation apparatus characterized by  
comprising:

- 3 -

image input means for inputting image data of a user;

voice input means for inputting voice data of the user;

5 living body information input means for inputting living body information of the user;

first estimation means for estimating a surrounding environment of the user on the basis of the image data, voice data, and living body information;

10 holding means for holding reference data serving as a reference used upon estimating a psychological state of the user;

second estimation means for estimating the psychological state of the user by comparing at least one of the image data, voice data, and living body information with the reference data; and

third estimation means for, when the psychological state of the user estimated by the second estimation means is a predetermined state, estimating a cause of the psychological state of the user on the basis of the surrounding environment estimated by the first estimation means.

In order to achieve an object of the present invention, for example, a method of controlling an estimation apparatus of the present invention comprises the following arrangement.

- 4 -

That is, a method of controlling an estimation apparatus, characterized by comprising:

an image input step of inputting image data of a user;

5 a voice input step of inputting voice data of the user;

a living body information input step of inputting living body information of the user;

a first estimation step of estimating a  
10 surrounding environment of the user on the basis of the image data, voice data, and living body information;

a holding step of holding reference data serving as a reference used upon estimating a psychological state of the user;

15 a second estimation step of estimating the psychological state of the user by comparing at least one of the image data, voice data, and living body information with the reference data; and

a third estimation step of estimating, when the  
20 psychological state of the user estimated in the second estimation step is a predetermined state, a cause of the psychological state of the user on the basis of the surrounding environment estimated in the first estimation step.

25 Other features and advantages of the present invention will be apparent from the following description taken in conjunction with the accompanying

drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

5 BRIEF DESCRIPTION OF DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Fig. 1 is a block diagram showing the functional arrangement of a system including an estimation apparatus according to the first embodiment of the present invention;

15 Fig. 2 is a flowchart of processing to be executed by an interface apparatus 1 in a normal mode;

Fig. 3 is a block diagram showing the functional arrangement of a condition analysis unit 1302;

20 Fig. 4A is a flowchart of processing to be executed by the interface apparatus 1 in an interaction mode;

Fig. 4B is a flowchart of processing to be executed by the interface apparatus 1 in the interaction mode;

25 Fig. 5 is a flowchart showing details of processing in step S119;

Fig. 6 is a block diagram showing the functional arrangement of a system including an interface apparatus according to the second embodiment of the present invention;

5        Fig. 7A is a flowchart of processing to be executed by an interface apparatus 600 according to the second embodiment of the present invention;

Fig. 7B is a flowchart of processing to be executed by the interface apparatus 600 according to  
10 the second embodiment of the present invention;

Fig. 8 is a block diagram showing the functional arrangement of a system including an interface apparatus according to the third embodiment of the present invention;

15        Fig. 9A is a flowchart of processing to be executed by an interface apparatus 800 according to the third embodiment of the present invention; and

Fig. 9B is a flowchart of processing to be executed by the interface apparatus 800 according to  
20 the third embodiment of the present invention.

#### BEST MODE FOR CARRYING OUT THE INVENTION

Preferred embodiments of the present invention will now be described in detail in accordance with the  
25 accompanying drawings.

[First Embodiment]



Fig. 1 is a block diagram showing the functional arrangement of a system including an estimation apparatus (to be referred to as an interface apparatus hereinafter) according to this embodiment. In the following description, assume that units which form an interface apparatus 1 shown in Fig. 1 are configured by hardware components. However, some or all of these units may be implemented by software.

Referring to Fig. 1, reference numeral 2 denotes a user. In the following description, the interface apparatus estimates a cause that has driven the user 2 to the current emotion, and makes communication with the user 2 in accordance with the estimated result. Reference numeral 3 denotes a measuring instrument which measures living body information including the body temperature, heart rate, blood pressure, perspiration, and the like of the user, and transmits the measured living body information to the interface apparatus 1. The measuring instrument 3 is attached to the user 2, and this living body information is periodically measured and is transmitted to the interface apparatus 1 by radio.

Reference numeral 1 denotes an interface apparatus according to this embodiment, which is roughly configured by a sensor block 1100, information storage block 1200, and information processing block 1300.

- 8 -

The sensor block 1100 is roughly classified to units (image input unit 1101, voice input/output unit 1102, and living body information acquisition unit 1103) for acquiring image information, voice  
5 information, and living body information of an external world concerned with an user, and units (thermometer 1104, hygrometer 1105, and illuminometer 1106) for measuring information of the external world.

The image input unit 1101 captures a physical  
10 space as a moving image, and captures a surrounding environment including the user 2 in the following description. As a result, the surrounding environment of the user 2 and the expression and body action of the user 2 can be obtained as an image. The image input  
15 unit 1101 has a person tracking function of tracking a specific person as needed.

The voice input/output unit 1102 collects voice information on the physical space, and outputs a voice on the basis of a voice signal output from the  
20 information processing block 1300. In the following description, the voice input/output unit 1102 collects voice information from the surrounding environment including the user 2, and outputs a message to the user 2.

25 The living body information acquisition unit 1103 serves as an I/F unit for receiving the aforementioned

living body information transmitted from the measuring instrument 3.

The thermometer 1104 measures the temperature of the external world of the interface apparatus 1. The  
5 hygrometer 1105 measures the humidity of the external world of the interface apparatus 1. The illuminometer 1106 measures the illuminance of the external world of the interface apparatus 1. In the following description, the temperature measured by the  
10 thermometer 1104, the humidity measured by the hygrometer 1105, and the illuminance measured by the illuminometer 1106 will be referred to as environment information together.

The information storage block 1200 stores various  
15 kinds of information obtained from the sensor block 1100, information to be stored in advance, and the like, and comprises an event log storage unit 1201, person data storage unit 1202, average person data storage unit 1203, and control information storage unit 1204.

20 The event log storage unit 1201 stores the living body information and environment information obtained from the sensor block 1100 as an event log together with the current date and time.

The person data storage unit 1202 stores personal  
25 data of the user 2 in advance. This personal data includes data required to specify the user 2, i.e., the face and whole body images of the user 2, feature

amount data of a voice of the user 2, and the like.

Also, this personal data includes physical information of the user 2 such as the body height, body weight, average body temperature, average pulse rate, and the

5 like of the user 2.

The average person data storage unit 1203 stores feature amount data of voices, expressions, actions, heart rates, and the like for respective emotions of an average person.

10 For example, voice features include voice pitch, loudness, frequency characteristic, and the like, and are given as data having certain ranges in association with respective emotions of delight, anger, sorrow, and pleasure. Also, expression features include motions of  
15 eyes, mouth, eyebrows, and the like, and are given as having certain ranges in association with respective emotions.

The control information storage unit 1204 sequentially stores the processing results of this  
20 interface apparatus 1 as control information. Note that the control information indicates "the determination result of the user's emotion of the interface apparatus 1", "its cause estimation result", "control contents required to remove the cause", and  
25 "control result", and is stored together with execution times of respective processes.

The information processing block 1300 is an execution block that executes respective processes to be implemented by the interface apparatus 1, and comprises a conversation analysis unit 1301, condition  
5 analysis unit 1302, cause estimation unit 1303, control information generation unit 1304, and control unit 1305.

The conversation analysis unit 1301 executes processing for analyzing the conversation contents on the basis of voice data input to this interface  
10 apparatus 1 via the voice input/output unit 1102. Since the conversation analysis processing is a state-of-the start technique, a description thereof will be omitted.

The condition analysis unit 1302 executes  
15 processing for estimating the emotion of the user 2, processing for estimating the surrounding environment of the user 2, and the like on the basis of information acquired from the sensor block 1100.

The cause estimation unit 1303 executes  
20 processing for estimating a cause of the emotion of the user 2 estimated by the condition analysis unit 1302.

The control information generation unit 1304 generates commands (control information) for executing processing contents to be executed by this interface  
25 apparatus 1 so as to remove the cause on the basis of the estimation result of the cause estimation unit 1303.

- 12 -

The control unit 1305 executes processing according to the commands (control information) generated by the control information generation unit 1304.

5           Then, the results of a series of processes done by the information processing block 1300, i.e., the emotion estimation result, cause estimation result based on the emotion estimation result, and control result based on the cause estimation result are  
10 recorded as one set in the control information storage unit 1204.

Note that only the user himself or herself can confirm details of data stored in the information storage block 1200 to protect his or her privacy, and  
15 only a determination result (e.g., something wrong has occurred or the like) is presented to other users. This presentation is made by a conversation or data transmission between the user 2 and interface apparatus 1. Data transmission can be made at a desired time and  
20 to a desired destination in accordance with settings if it is set in advance. Since the information processing block 1300 comprises person identifying unit as following description, the privacy problem can be avoided even if a person is not identified using a  
25 password or the like.

The processing to be executed by this interface apparatus 1 will be described below. The following

explanation will be given under the assumption that the interface apparatus 1 is equipped in a classroom of a school for the sake of simplicity. Therefore, the measuring instruments 3 are attached to all students  
5 (including the user 2) in the classroom, and the person data storage unit 1202 stores personal data of all the students in the classroom.

Under such settings, the interface apparatus 1 executes processing for always collecting image and  
10 voice data in the classroom, and storing condition information based on image and voice data at that time and living body information already transmitted from the measuring instrument 3 at that time in the event log storage unit 1201 together with date and time data.  
15 A mode that collects the conditions in the classroom in this way is called a normal mode. Therefore, the interface apparatus 1 executes processing for collecting the conditions in the classroom in the normal mode.

20 Fig. 2 is a flowchart of processing to be executed by the interface apparatus 1 in the normal mode.

The interface apparatus 1 executes processing for collecting the conditions in the classroom (step S101).  
25 More specifically, the interface apparatus 1 receives image data in the classroom via the image input unit 1101 and voice data via the voice input/output unit

1102. Also, the interface apparatus 1 receives living body information of respective students periodically transmitted from the measuring instrument 3 attached to the respective students. Furthermore, the interface apparatus 1 measures the temperature, humidity, and illuminance by the thermometer 1104, hygrometer 1105, and illuminometer 1106.

Next, the condition analysis unit 1302 executes processing for estimating the conditions in the image data acquired from the image input unit 1101 (step S103). Details of the processing in step S103 will be described below.

Fig. 3 is a block diagram showing the functional arrangement of the condition analysis unit 1302. The condition analysis unit 1302 comprises a data loading section 301, person identifying section 302, and condition estimation section 303. Furthermore, the data loading section 301 comprises an environment information data loader 301a and stored data loader 301b.

The environment information data loader 301a loads an information group obtained from the sensor block 1100. The stored data loader 301b loads an information group recorded in the information storage block 1200.

The person identifying section 302 specifies a student who appears in an image by collating image and



voice data input from the sensor block 1100 with  
personal data input from the stored data loader 301b.

For example, since a face region of a person who  
appears in an image input from the sensor block 1100  
5 can be specified by a known technique, the face image  
in this face region is compared with those of  
respective students (included in personal data of the  
respective students) to identify the face in this face  
region. Since the technique for identifying the face  
10 that appears in an image in this way is known to those  
who are skilled in the art, a detailed description  
thereof will be omitted.

A feature amount is extracted from the voice  
signal input from the sensor block 1100 by a known  
15 technique, and the extracted feature amount is compared  
to those of voice data of the respective students  
(included in personal data of the respective students)  
to identify the voice signal input from the sensor  
block 1100. Since the technique for identifying the  
20 voice of the collected voice signal in this way is  
known to those who are skilled in the art, a detailed  
description thereof will be omitted.

In this manner, an individual who appears in the  
image is identified.

25 The condition estimation section 303 estimates  
the emotion of the individual identified by the person  
identifying section 302 on the basis of the information

group input from the sensor block 1100. That is, the condition estimation section 303 analyzes the image and voice data of the individual input from the sensor block 1100 to make emotion recognition, i.e., if this individual is laughing or angry. For example, if the eyes are slanting down outwards, the mouth is open widely, the voice is loud and the frequency characteristic has a high level in the high-frequency range, and the action is brisk, it is determined that the individual is "cheerful". Since the technique for making emotion recognition of the individual using image and voice data in this way is a state-of-the-art technique, a description thereof will be omitted.

In some cases, the identified individuals may be in the middle of a conversation. In such case, action recognition of each individual must be made.

With this processing, a person who appears in the image can be identified, and the emotion of the identified person can be estimated.

Referring back to Fig. 2, processing for recording the analysis result of the condition estimation section 303 in the event log storage unit 1201 as a log is executed (step S104). Upon recording the analysis result as a log, a recording date and time are additionally recorded. The date and time are measured by the control unit 1305.

- 17 -

A log to be recorded has contents, for example, "O/O, O:O, A and B had a cheerful conversation". Also, for example, upon recording such log, it is determined based on the log contents "A", "B", and "cheerful" that  
5 A and B are in good terms, and data that advises accordingly is recorded together with the log.

In this manner, the emotion of each student who appears in the image obtained from the image input unit 1101 and the conditions in the classroom can be  
10 estimated.

The interaction mode as a mode in which this interface apparatus 1 has a conversation with the user 2 will be described below. Note that this interaction mode indicates a mode for a contact between the user 2  
15 and this interface apparatus 1, e.g., a dialogue, communication, or the like. Switching to the interaction mode can be attained by operating a switch or the like (not shown). Hence, processing is normally done in the normal mode, and when a conversation is to  
20 be made using this interface apparatus 1, the control transits to the interaction mode by operating a switch or the like. Note that the means and method for making transition to the interaction mode are not limited to this.

25 At this time, since this interface apparatus 1 has a conversation with the user 2, the image input unit 1101 captures an image including the user 2, and

- 18 -

the voice input/output unit 1102 collects voice data from the user 2 (of course, voice data other than that of the user 2 is also collected).

Figs. 4A and 4B are flowcharts of processing to  
5 be executed by the interface apparatus 1 in the interaction mode.

The interface apparatus 1 executes processing for collecting the conditions in the classroom (step S112). More specifically, the interface apparatus 1 receives  
10 image data in the classroom via the image input unit 1101 and voice data via the voice input/output unit 1102. Also, the interface apparatus 1 receives living body information of respective students periodically transmitted from the measuring instrument 3 attached to  
15 the respective students. Furthermore, the interface apparatus 1 measures the temperature, humidity, and illuminance, in the classroom, by the thermometer 1104, hygrometer 1105, and illuminometer 1106.

Next, the interface apparatus 1 executes the  
20 person identifying processing in image data which is executed in step S103, and also the processing for recording information indicating the identified person in the event log storage unit 1201 (step S113). The control unit 1305 checks if the apparatus previously  
25 communicated with the person identified in step S113 (step S114). This processing is done by checking if "information indicating persons with whom the apparatus

previously communicated" recorded in the event log storage unit 1201 includes information indicating the currently identified person.

As a result, if no information indicating the currently identified person is recorded in the event log storage unit 1201 as a log (if the apparatus communicates with the currently identified person for the first time), the flow advances to step S115a, and the condition analysis unit 1302 reads out average person data stored in the average person data storage unit 1203 (step S115a). On the other hand, if the information indicating the currently identified person is recorded in the event log storage unit 1201 as a log (if the apparatus previously communicated with the currently identified person), the flow advances to step S115b, and the condition analysis unit 1302 reads out personal data of the currently identified person from the person data storage unit 1202 (step S115b).

The condition analysis unit 1302 executes the processing for estimating the emotion of the person in the image, which is executed in step S103, using the image information, voice information, living body information, and environment information obtained in step S112 and average person data obtained in step S115a or personal data obtained in 115b (step S116). In this case, the emotion of the user 2, which is

determined from the image obtained from the image input unit 1101, is estimated.

However, although one's psychological state is directly linked with emotions in many cases, emotions  
5 may sometimes appear while internally masking a real psychological state, and this mode aims at finding it out. For example, even when the emotion estimated from the image is "cheerful, happily", if the pulse rate is high, the body temperature is relatively low, and the  
10 frequency characteristic of the voice is unnaturally high in the high-frequency range, the psychological state of the person is estimated that he or she may be forcing a laugh. In this manner, when the emotion is to be estimated using a plurality of pieces of  
15 information, an emotion estimated based on given referred information may be opposite to that estimated using another information.

Hence, in this embodiment, if an emotion estimated from the image data, that estimated from the  
20 voice data, and that estimated from the living body information include at least one negative emotion (down, sad, or the like), it is determined that "something wrong has occurred" (step S118), and the flow advances to step S119. On the other hand, if emotions are  
25 estimated using respective pieces of information, and they indicate roughly equal emotions independently of information used, this processing ends.

Furthermore, a change in psychological state can be checked by comparing the current data of the user 2 with his or her old data. For example, even if the user 2 replies "Good", if it is determined as a result of expression analysis that the reply is in low spirits since the eyes look hollow, the voice is soft, the frequency characteristic has a high level in the low-frequency range, and so forth, or if a feature indicating that a sweating amount is larger than an ordinary one is extracted from the image information or living body information, the condition estimation section 303 estimates that "The user appears depressed. That may be a trouble that he (or she) cannot talk to others", and also estimates that "something wrong has occurred in the psychological state".

In case of "something wrong has occurred", the cause estimation unit 1303 executes processing for estimating a cause that drives to the negative emotion estimated in step S116 (step S119). For example, if the plurality of emotions estimated for the user 2 by the condition analysis unit 1302 include an estimation result "down", the cause estimation unit 1303 estimates its cause.

Fig. 5 is a flowchart showing details of the processing in step S119. If only one of the emotion estimated from the image data, that estimated from the voice data, and that estimated from the living body

information is a negative emotion (step S501), the flow advances to step S506, and the cause estimation unit 1303 determines that a message for the purpose of caring about this negative emotion (e.g., a message  
5 "Are you OK?" or the like) is to be output to the voice input/output unit 1102, and outputs information that advises accordingly to the control information generation unit 1304 (step S506).

On the other hand, if two or more of the emotion  
10 estimated from the image data, that estimated from the voice data, and that estimated from the living body information include negative emotions (step S501), the flow advances to step S502 to check the physical condition of the user 2 with reference to the living  
15 body information input in step S112 (step S502). More specifically, the physical condition of the user 2 is checked by comparing the average body temperature and average pulse rate included in the personal data of the user 2 stored in the person data storage unit 1202 with  
20 the body temperature and pulse rate included in the living body information input in step S112. Note that the cause estimation unit 1303 holds in advance as data whether the physical condition is good/bad depending on the relationship between the body temperature and pulse  
25 rate, and average ones.

As a result of checking, if the current body temperature of the user 2 is largely different from the



average body temperature (i.e., the user is running a fever), and the pulse rate is largely different from the average pulse rate (i.e., the pulse rate is not stable), it is determined that the physical condition of the user 2 is bad (step S502), and the flow advances to step S507. In step S507, it is determined that a message informing the bad physical condition is to be output, and information that advises accordingly is output to the control information generation unit 1304 (step S507).

On the other hand, if the current body temperature of the user 2 is nearly the same as the average body temperature (i.e., the user is not running a fever), and the pulse rate is nearly the same as the average pulse rate (i.e., the pulse rate is stable), it is determined that the physical condition of the user 2 is good, and the flow advances to step S503. In step S503, information associated with previous control for similar emotions is searched for with reference to information associated with the user 2 of those held by the control information storage unit 1204 (step S503). If the information associated with previous control for similar emotions is found, the flow advances to step S508, and the found information is output to the control information generation unit 1304 (step S508).

On the other hand, if no information associated with previous control for similar emotions is found,

the flow advances to step S505, and all logs associated with the user 2 of those held by the event log storage unit 1201 are extracted to estimate a cause (step S505). When a log "O/O, O:O, A and B had a cheerful conversation" of old logs associated with the user 2 is recorded together with a log "A and B are in good terms", but a recent log "x/x, x:x, A and B have a quarrel" is recorded together with a log "A and B are at strife", it is estimated that A is depressed owing to this quarrel.

In this manner, when the logs associated with the user 2 are referred to, and a log (second log) indicating a condition opposite to that indicated by the referred log (first log) is recorded later, the condition recorded in the second log is estimated as a cause.

In this manner, the cause of the current emotion of the user 2 can be estimated. Note that the cause estimation method is not limited to this, and various other methods may be used. For example, logs which are associated with the user 2 and are recorded in the event log storage unit 1201 during a predetermined period of time before the time at which the estimated emotion changed, and the condition indicated by logs in a group with a largest number of logs of those which indicate similar conditions may be estimated as a cause. That is, various other methods may be used.

Upon completion of the processing according to the flowchart shown in Fig. 5, the flow returns to step S120 in Fig. 4B, and the control information generation unit 1304 generates a command (control information) which makes the control unit 1305 execute processing to be executed on the basis of the information received from the condition analysis unit 1302 (step S120).

For example, since the information indicating that a message for the purpose of caring about this negative emotion (e.g., a message "Are you OK?" or the like) is to be output to the voice input/output unit 1102 is input to the control information generation unit 1304 in step S506, the control information generation unit 1304 generates a command for making the control unit 1305 issue such message, and outputs that command to the control unit 1305.

Since the information indicating that a message informing the bad physical condition is to be output is input to the control information generation unit 1304 in step S507, the control information generation unit 1304 generates a command for making the control unit 1305 execute processing for outputting a message informing the bad physical condition, and outputs that command to the control unit 1305.

Since the information found in step S503 is input to the control information generation unit 1304 in step S508, the control information generation unit 1304

- 26 -

generates a command for making the control unit 1305 execute control processing according to this information, and outputs that command to the control unit 1305.

5           Hence, the control unit 1305 executes processing according to the command received from the control information generation unit 1304 (step S121).

          For example, upon reception of the command required to output a message for the purpose of caring  
10   about this negative emotion (e.g., a message "Are you OK?" or the like) to the voice input/output unit 1102, the control unit 1305 reads out message data according to this command from its internal memory, and outputs it to the voice input/output unit 1102. The voice  
15   input/output unit 1102 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.

          Upon reception of the command required to execute processing for outputting a message informing the bad  
20   physical condition, the control unit 1305 reads out message data for informing the bad physical condition of the user 2 (e.g., "the physical condition of the user 2 is bad") from its internal memory, and outputs it to the voice input/output unit 1102. The voice  
25   input/output unit 1102 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.

- 27 -

Upon reception of the information found in step S503, the control unit 1305 executes control for previous similar emotions.

The control unit 1305 records the contents of a series of the processes, i.e., data for identifying the individual (the user 2 in this case) identified in step S113, the interaction contents for this individual, the emotion estimation result for this individual in step S116, and the cause estimation result of this emotion in step S119, in the control information storage unit 1204 as a log of the current processing (step S122). This recorded log is referred to when it is searched in step S503 for previous information indicating persons and their emotions, and control processing executed depending on causes.

The information storage block 1200 has performance that stores all pieces of environment information, conversation contents, and the like, but informs persons other than the authenticated user himself or herself of only the condition analysis result and control information and protects individual privacy such as the living body information and conversation contents. For example, assume that the user 2 asks the interface apparatus 1 "O looked depressed O/O, and what were you talking about?". However, when the user 2 is determined by the person identifying section 302 as a person other than the user

himself or herself, the apparatus limits disclosure of information to "O was depressed O/O. But he (or she) became cheerful after conversation for about 30 minutes", and does not disclose any conversation contents. By providing the privacy protection function, the user can express true feelings with a sense of security.

In this embodiment, the means for informing the user 2 of a message uses a voice. However, a display device may be newly added to this interface apparatus 1, and a message may be displayed on the display device as a text message. The informing method is not particularly limited.

[Second Embodiment]

This embodiment uses the interface apparatus in use application different from the first embodiment.

Fig. 6 is a block diagram showing the functional arrangement of a system including an interface apparatus according to this embodiment. In the following description, assume that units which form an interface apparatus 600 shown in Fig. 6 are configured by hardware components. However, some or all of these units may be implemented by software. Also, the same reference numerals in Fig. 6 denote the same parts as in Fig. 1, and a description thereof will be omitted.

Referring to Fig. 6, reference numeral 4 denotes an infant as a person to be aided. In the following

description, the interface apparatus 600 assists  
child-care help for this infant 4. The same measuring  
instruments 3 as in the first embodiment is attached to  
this infant 4, and living body information about this  
5 infant 4 is periodically transmitted to the interface  
apparatus 600 by radio.

Reference numeral 7 denotes a person who cares  
for this infant 4 (e.g., the mother of the infant 4).  
The caretaker 7 always carries a data receiver 5 which  
10 receives data transmitted from the interface apparatus  
600, and visually/audibly outputs the received data.  
In this embodiment, the control unit 1305 has an  
external communication function, i.e., a data  
transmission function to this data receiver 5.

15 Reference numeral 6 denotes a feeding bottle with  
a sensor. This feeding bottle 6 has a sensor which  
measures a quantity of milk currently stored in this  
feeding bottle, and periodically transmits the measured  
quantity to the interface apparatus 600. Note that  
20 this sensor is not particularly limited, and it may be  
a sensor that measures any quantity as long as it can  
specify the quantity of milk such as the volume, weight,  
or the like.

The differences of the interface apparatus 600  
25 from the interface apparatus 1 of the first embodiment  
are that an infant data storage unit 601 that stores  
data associated with the infant 4 is equipped in place

- 30 -

of the person data storage unit 1202, and an average infant data storage unit 602 is equipped in place of the average person data storage unit 1203.

Figs. 7A and 7B are flowcharts of processing to be executed by the interface apparatus 600 according to this embodiment.

The image input unit 1101 inputs an image of a surrounding environment including the infant 4, the voice input/output unit 1102 inputs a voice of the infant 4, the living body information acquisition unit 1103 inputs living body information including the body temperature, pulse rate, and the like of the infant 4 transmitted from the measuring instrument 3, and the feeding bottle 6 with a sensor inputs the quantity of milk. Hence, these data are stored in the event log storage unit 1201 as a log together with recording date and time data (step S201).

Upon recording this log, the condition analysis unit 1302 recognizes with reference to the image from the image input unit 1101 whether or not the infant 4 is eating, whether or not he or she is crying, whether or not a diaper is being changed, and the like, and records the recognition result (infant state) together with this log. In order to recognize the condition in an image such as the action, gesture, and the like of a person in the image, a technique for recognizing the condition in a given image using a neural network that



- 31 -

has learned images under various conditions may be used. However, the present invention is not limited to such specific technique.

When this recognition result is "something is  
5 wrong with the infant 4", e.g., "the infant 4 is  
crying" in this embodiment, the flow advances to step  
S205. In order to precisely recognize that the infant  
is crying, the voice information obtained from the  
voice input/output unit 1102 may also be referred to.  
10 As for a technique for recognizing based on the voice  
information whether or not this voice is a crying voice,  
a technique for recognizing whether a given voice is a  
crying or laughing voice using a neural network that  
has learned voices under various conditions may be used.  
15 However, the present invention is not limited to such  
specific technique.

When it is recognized that the infant 4 is crying,  
the cause estimation unit 1303 executes processing for  
estimating a cause of crying.

20 The cause estimation unit 1303 checks with  
reference to the log recorded in the event log storage  
unit 1201 if a meal is required (step S205). More  
specifically, the cause estimation unit 1303 specifies  
a start time of the meal with reference to the log.  
25 Then, the cause estimation unit 1303 specifies the  
quantity of milk at the specified time. Next, the  
cause estimation unit 1303 specifies an end time of the

meal and also the quantity of milk at the specified time. Then, the cause estimation unit 1303 can calculate the quantity of the previous meal by calculating the difference between the specified  
5 quantities of milk.

On the other hand, since data which is associated with this infant 4 and stored in the infant data storage unit 601 includes data indicating the quantity of a single meal, the cause estimation unit 1303 checks  
10 if the calculated quantity of the previous meal is equal to or smaller than that of the single meal indicated by this data.

If the calculated quantity of the previous meal is equal to or smaller than that of the single meal  
15 indicated by this data, the cause estimation unit 1303 estimates that the infant is crying since he or she is hungry.

Note that the method of checking if the infant is hungry is not limited to this. The following method  
20 may be used. That is, a possibility indicating if the current time is a meal time is calculated by:

Possibility of meal time = (previous meal quantity/elapsed time from previous meal)/(average meal quantity/meal interval)

25 The "previous meal quantity" is calculated as described above. As for the "elapsed time from previous meal", since the end time of the meal can be

specified from the log, and the current time is measured, the difference between these times can be calculated as the elapsed time. The "average meal quantity" and "meal interval" are obtained from the  
5 previous logs of the meal quantity and meal time of the infant 4.

As a calculation result of the above equation, if the possibility is equal to or lower than 1.2, it is determined that the current time is the meal time.

10 As a result of the above processing, if the cause of crying is a meal, the flow advances to step S250, and the cause estimation unit 1303 outputs information advising that the cause of crying is a meal to the control information generation unit 1304 (step S250).

15 On the other hand, if the cause of crying is not a meal, the flow advances to step S206 to check if the cause of crying is a diaper (step S206). The cause estimation unit 1303 specifies the last time the diaper was changed with reference to the log recorded in the  
20 event log storage unit 1201. The cause estimation unit 1303 calculates the difference between the specified time and current time, and checks if the difference is equal to or larger than a predetermined value, i.e., if a time has sufficiently elapsed from the previous  
25 diaper change time. As this predetermined value, the average value of diaper change time intervals is used. However, the present invention is not limited to this.

- 34 -

Note that the method of estimating whether or not the cause is a diaper is not limited to this.

If the cause of crying is a diaper, the flow advances to step S251, and the cause estimation unit  
5 1303 outputs information advising that the cause of crying is a diaper to the control information generation unit 1304 (step S251).

On the other hand, if the cause of crying is not a diaper, the flow advances to step S207 to check if  
10 the cause of crying is lack of sleep (step S207). The previous sleeping time is calculated by calculating the difference between the last falling-asleep time and the wake-up time with reference to the log recorded in the event log storage unit 1201. It is then checked if the  
15 calculated sleeping time is equal to or shorter than a predetermined value, i.e., if the previous sleeping time is not sufficient. As this predetermined value, the average value of the intervals of the sleeping start and end times recorded in old logs is used.  
20 However, the present invention is not limited to such specific value.

Note that the method of estimating whether or not the cause is lack of sleep is not limited to this.

If the cause of crying is lack of sleep, the flow  
25 advances to step S252, and the cause estimation unit 1303 outputs information advising that the cause of

crying is lack of sleep to the control information generation unit 1304 (step S252).

On the other hand, if the cause of crying is not lack of sleep, the flow advances to step S208 to check  
5 the physical condition of the infant 4 with reference to the living body information input in step S201 (step S208). More specifically, the physical condition of the infant 4 is checked by comparing the average body temperature and average pulse rate included in the  
10 personal data of the infant 4 stored in the infant data storage unit 601, and the body temperature and pulse rate included in the living body information input in step S201. Note that the cause estimation unit 1303 holds in advance as data whether the physical condition  
15 is good/bad depending on the relationship between the body temperature and pulse rate, and average ones.

As a result of checking, if the current body temperature of the infant 4 is largely different from the average body temperature (i.e., the infant is  
20 running a fever), and the pulse rate is largely different from the average pulse rate (i.e., the pulse rate is not stable), it is determined that the physical condition of the infant 4 is bad and a message informing the bad physical condition is to be output,  
25 and information that advises accordingly is output to the control information generation unit 1304 (step S208).

Next, the control information generation unit 1304 generates a command (control information) which makes the control unit 1305 execute processing to be executed on the basis of the information received from  
5 the condition analysis unit 1302, and transmits the generated command to the control unit 1305. Then, the control unit 1305 executes processing according to this command (step S209).

For example, since information indicating that  
10 the cause of crying is a meal is input to the control information generation unit 1304 in step S250, the control information generation unit 1304 generates a command for making the control unit 1305 execute processing for transmitting a message "give the infant  
15 4 a meal" to the data receiver 5, and outputs the command to the control unit 1305.

Since information indicating that the cause of crying is a diaper is input to the control information generation unit 1304 in step S251, the control  
20 information generation unit 1304 generates a command for making the control unit 1305 execute processing for transmitting a message "change a diaper" to the data receiver 5, and outputs the command to the control unit 1305.

25 Since information indicating that the cause of crying is lack of sleep is input to the control information generation unit 1304 in step S252, the

- 37 -

control information generation unit 1304 generates a command for making the control unit 1305 execute processing for transmitting data of a lullaby to the data receiver 5, and outputs the command to the control  
5 unit 1305.

Since information indicating that the cause of crying is the bad physical condition of the infant 4 is input to the control information generation unit 1304 in step S208, the control information generation unit  
10 1304 generates a command for making the control unit 1305 execute processing for transmitting a message "the physical condition of the infant 4 is bad" to the data receiver 5, and outputs the command to the control unit 1305.

15 Hence, the control unit 1305 executes processing according to the command received from the control information generation unit 1304.

For example, upon reception of the command for making the control unit 1305 execute processing for  
20 transmitting a message "give the infant 4 a meal" to the data receiver 5, the control unit 1305 reads out message data according to this command from its internal memory, and transmits it to the data receiver 5. As a result, the data receiver 5 generates a voice  
25 according to this message data by a speech synthesis technique or the like, and outputs the voice.

Upon reception of the command for making the control unit 1305 execute processing for transmitting a message "change a diaper" to the data receiver 5, the control unit 1305 reads out message data according to this command from its internal memory, and transmits it to the data receiver 5. As a result, the data receiver 5 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.

10        Upon reception of the command for making the control unit 1305 execute processing for transmitting data of a lullaby to the data receiver 5, the control unit 1305 reads out its own data of the lullaby, and transmits it to the data receiver 5. As a result, the data receiver 5 plays back and outputs this data of the lullaby.

      Upon reception of the command for making the control unit 1305 execute processing for transmitting a message "the physical condition of the infant 4 is bad" to the data receiver 5, the control unit 1305 reads out message data according to this command from its internal memory, and transmits it to the data receiver 5. As a result, the data receiver 5 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.



In this manner, the caretaker 7 who holds the data receiver 5 can be informed of the state of the infant 4.

The control unit 1305 executes processing for recording information corresponding to that used as the previous log in the processing of those used in a series of processes in the event log storage unit 1201. [Third Embodiment]

This embodiment uses the interface apparatus in a use application different from the first and second embodiments.

Fig. 8 is a block diagram showing the functional arrangement of a system including an interface apparatus according to this embodiment. In the following description, assume that units which form an interface apparatus 800 shown in Fig. 8 are configured by hardware components. However, some or all of these units may be implemented by software. Also, the same reference numerals in Fig. 8 denote the same parts as in Fig. 1, and a description thereof will be omitted.

Referring to Fig. 8, reference numeral 2 denotes a user indoors. In the following description, the interface apparatus 800 assists all the members including the user 2 to spend the time comfortably indoors. Note that "indoor" means an air-conditioned space, and the same applies to the following

description if this space is an interior of a train, vehicle, or the like.

Figs. 9A and 9B are flowcharts of processing to be executed by the interface apparatus 800 according to  
5 this embodiment.

The image input unit 1101 inputs an image of a surrounding environment including the user 2, the voice input/output unit 1102 inputs a voice of the user 2, the living body information acquisition unit 1103  
10 inputs living body information such as body temperature, pulse count and the like of the user 2 transmitted from the measuring instrument 3. The indoor temperature, humidity, and illuminance are input from the thermometer 1104, hygrometer 1105, and illuminometer  
15 1106. Hence, these data are stored in the event log storage unit 1201 as a log together with recording date and time data (step S301).

Upon recording this log, the condition analysis unit 1302 recognizes with reference to the image from  
20 the image input unit 1101 whether the user 2 feels hot or cold, whether the interior of the room is bright or dark, and so forth, and records the recognition result together with this log.

For example, if sweat on the forehead of the user  
25 2 is recognized from the image input from the image input unit 1101, and the temperature input from the thermometer 1104 is 27°C or higher, it is recognized

that "the user 2 feels hot". The action of the user 2 is recognized, and if the recognition result is an arm-rubbing action, and the temperature input from the thermometer 1104 is 25°C or lower, it is recognized  
5 that "the user 2 feels cold". In this manner, the emotion of the user 2 is estimated using information input from the sensor block 1100.

As for indoor conditions, when the humidity input from the hygrometer 1105 exceeds, e.g., 80%, it is  
10 recognized that "the humidity is high". Also, when the illuminance input from the illuminometer 1106 is equal to or lower than a predetermined value, it is determined that "the interior of the room is dark".

In order to recognize the condition in an image  
15 such as the action, gesture, and the like of a person in the image, a technique for recognizing the condition in a given image using a neural network that has learned images under various conditions may be used. However, the present invention is not limited to such  
20 specific technique.

If this recognition result indicates that "something is wrong with the user 2", i.e., if one of "the user feels hot (cold)", "the humidity is high (low)", and "the interior of the room is dark" is the  
25 analysis result of the condition analysis unit 1302, the condition analysis unit 1302 determines that "something is wrong with the user 2".

The aforementioned processing is applied to persons other than the user 2 in the image input from the image input unit 1101, and if it is determined that "something is wrong with more than half of all persons  
5 in the image", the flow advances to step S305.

The cause estimation unit 1303 executes processing for estimating a cause of something wrong of respective persons in the room.

The cause estimation unit 1303 checks with  
10 reference to the log recorded in the event log storage unit 1201 in step S301 previously if the cause of something wrong is "the user 2 (or a user other than the user 2; the user 2 as the representative in this case) feels hot or cold" (step S305). As a result, if  
15 "the user 2 feels hot or cold", the flow advances to step S350. In step S350, information that advises to decrease the room temperature by adjusting an air conditioner if the user 2 feels hot, or to increase the room temperature by adjusting the air conditioner if  
20 the user 2 feels cold is output to the control information generation unit 1304 (step S350).

On the other hand, if the cause of something wrong is not "the user 2 feels hot or cold", the flow advances to step S306, and the cause estimation unit  
25 1303 checks with reference to the log recorded in the event log storage unit 1201 in step S301 previously if the cause of something wrong is "the humidity is high

or low" (step S306). As a result, if "the humidity is high or low", the flow advances to step S351. In step S351, information that advises to dehumidify by adjusting the air conditioner if the humidity is high, or to humidify by adjusting the air conditioner if the humidity is low is output to the control information generation unit 1304 (step S351).

On the other hand, if the cause of something wrong is not the humidity, the flow advances to step S307, and the cause estimation unit 1303 checks with reference to the log recorded in the event log storage unit 1201 in step S301 previously if the cause of something wrong is "the interior of the room is dark" (step S307). As a result, if "the interior of the room is dark", the flow advances to step S352, and information that advises to make the interior of the room brighter by adjusting an illumination is output to the control information generation unit 1304 (step S352).

Next, the control information generation unit 1304 generates a command (control information) which makes the control unit 1305 execute processing to be executed on the basis of the information received from the condition analysis unit 1302, and transmits the generated command to the control unit 1305. Then, the control unit 1305 executes processing according to this command (step S309).

For example, since the information that advises to increase/decrease the room temperature by adjusting the air conditioner is input to the control information generation unit 1304 in step S350, the control  
5 information generation unit 1304 generates a command for making the control unit 1305 issue a message "increase/decrease the room temperature", and outputs the message to the control unit 1305.

Since the information that advises to  
10 dehumidify/humidify by adjusting the air conditioner is input to the control information generation unit 1304 in step S351, the control information generation unit 1304 generates a command for making the control unit 1305 issue a message "dehumidify/humidify", and outputs  
15 the message to the control unit 1305.

Since the information that advises to make the interior of the room brighter is input to the control information generation unit 1304 in step S351, the control information generation unit 1304 generates a  
20 command for making the control unit 1305 issue a message "make the interior of the room brighter", and outputs the message to the control unit 1305.

Hence, the control unit 1305 executes processing according to the command received from the control  
25 information generation unit 1304.

For example, upon reception of the command required to issue the message "increase/decrease the

room temperature", the control unit 1305 reads out data of this message from its internal memory, and outputs it to the voice input/output unit 1102. The voice input/output unit 1102 generates a voice according to  
5 this message data by a speech synthesis technique or the like, and outputs the voice.

Upon reception of the command required to issue the message "increase/decrease the room humidity", the control unit 1305 reads out data of this message from  
10 its internal memory, and outputs it to the voice input/output unit 1102. The voice input/output unit 1102 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.

15 Upon reception of the command required to issue the message "make the interior of the room brighter", the control unit 1305 reads out data of this message from its internal memory, and outputs it to the voice input/output unit 1102. The voice input/output unit  
20 1102 generates a voice according to this message data by a speech synthesis technique or the like, and outputs the voice.

In this way, the interior of the room can be maintained comfortable. Note that the control unit  
25 1305 may directly control the temperature or humidity in place of issuing the aforementioned messages.

The control unit 1305 executes processing for recording information corresponding to that used as the previous log in the processing of those used in a series of processes in the event log storage unit 1201.

5 [Fourth Embodiment]

The interface apparatus according to each of the above embodiments may be built in, e.g., a personal computer, monitoring camera, or the like as a single built-in device.

10 [Other Embodiments]

The objects of the present invention are also achieved when a CPU or MPU of a computer reads out and executes a program code from a recording medium (or storage medium), which records a program code of a software program that can implement the functions of the above-mentioned embodiments. In this case, the program code itself read out from the recording medium implements the functions of the above-mentioned embodiments, and the recording medium which stores the program code constitutes the present invention.

The functions of the above-mentioned embodiments may be implemented not only by executing the readout program code by the computer, but also by some or all of actual processing operations executed by an operating system (OS) running on the camera on the basis of an instruction of the program code.



Furthermore, the functions of the above-mentioned embodiments may be implemented by some or all of actual processing operations executed by a CPU or the like arranged in a function extension card or a function extension unit, which is inserted in or connected to the computer, after the program code read out from the recording medium is written in a memory of the extension card or unit.

When the present invention is applied to the recording medium, that recording medium stores program codes corresponding to the aforementioned flowchart (functional arrangement).

As many apparently widely different embodiments of the present invention can be made without departing from the spirit and scope thereof, it is to be understood that the invention is not limited to the specific embodiments thereof except as defined in the claims.

#### 20 Claim of Priority

This application claims priority from Japanese Patent Application No. 2004-312858 filed on October 27, 2004, which is hereby incorporated by reference herein.

## CLAIMS

1. An estimation apparatus characterized by comprising:
- 5 image input means for inputting image data of a user;
- voice input means for inputting voice data of the user;
- living body information input means for inputting
- 10 living body information of the user;
- first estimation means for estimating a surrounding environment of the user on the basis of the image data, voice data, and living body information;
- holding means for holding reference data serving
- 15 as a reference used upon estimating a psychological state of the user;
- second estimation means for estimating the psychological state of the user by comparing at least one of the image data, voice data, and living body
- 20 information with the reference data; and
- third estimation means for, when the psychological state of the user estimated by said second estimation means is a predetermined state, estimating a cause of the psychological state of the
- 25 user on the basis of the surrounding environment estimated by said first estimation means.

- 49 -

2. The apparatus according to claim 1,  
characterized in that the predetermined state is a  
state in which at least one of an emotion estimated by  
said second estimation means based on the image data,  
5 an emotion estimated by said second estimation means  
based on the voice data, and an emotion estimated by  
said second estimation means based on the living body  
information are negative emotions.

10 3. The apparatus according to claim 1,  
characterized by further comprising informing means for  
informing a result estimated by said third estimation  
means.

15 4. The apparatus according to claim 1,  
characterized by further comprising fourth estimation  
means for, when the psychological state of the user  
estimated by said second estimation means is the  
predetermined state, estimating based on the living  
20 body information whether or not a physical condition of  
the user is bad.

5. The apparatus according to claim 4,  
characterized by further comprising informing means for  
25 informing a result estimated by said fourth estimation  
means.

- 50 -

6. A method of controlling an estimation apparatus, characterized by comprising:

an image input step of inputting image data of a user;

5 a voice input step of inputting voice data of the user;

a living body information input step of inputting living body information of the user;

a first estimation step of estimating a  
10 surrounding environment of the user on the basis of the image data, voice data, and living body information;

a holding step of holding reference data serving as a reference used upon estimating a psychological state of the user;

15 a second estimation step of estimating the psychological state of the user by comparing at least one of the image data, voice data, and living body information with the reference data; and


a third estimation step of estimating, when the  
20 psychological state of the user estimated in the second estimation step is a predetermined state, a cause of the psychological state of the user on the basis of the surrounding environment estimated in the first estimation step.

25


7. A program characterized by making a computer execute a control method of claim 6.

8. A computer-readable storage medium  
characterized by storing a program of claim 7.

1/12


**FIG. 1**

2/12

**FIG. 2**

3/12


FIG. 3






4/12

FIG. 4A




5/12

FIG. 4B




6/12

FIG. 5




7/12

**FIG. 6**


8/12

FIG. 7A




9/12

FIG. 7B




10/12

**FIG. 8**

11/12


FIG. 9A





12/12

FIG. 9B



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/JP2005/019941

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> Int.Cl. <b>G06N5/04</b> (2006.01), <b>A61B5/16</b> (2006.01) According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) Int.Cl. <b>G06N5/04</b> (2006.01), <b>A61B5/16</b> (2006.01) Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched <small>Published examined utility model applications of Japan 1922-1996 Published unexamined utility model applications of Japan 1971-2005 Registered utility model specifications of Japan 1996-2005 Published registered utility model applications of Japan 1994-2005</small> Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	JP 2003-237588 A (SONY CORP) 2003.08.27, paragraph [ 0023] -[ 0024] ,[ 0032] -[ 0041] & DE 10306958 A1 & US 2003/218544 A1	1-8
Y	JP 2001-344352 A (TOSHIBA CORP) 2001.12.14, paragraph [ 0052] ,[ 0089] ,[ 0104] -[ 0105] & US 2001/049471 A1 & US 2003/204132 A1 & US 2003/194205 A1 & US 2003/195398 A1	1-8
Y	JP 2002-215183 A (A.G.I. Inc) 2002.07.31, paragraph [ 0079] -[ 0080] & EP 1318505 A1 & US 2003/182123 A1 & US 2003/194205 A1 & WO 2002/023524 A1	2
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 15.11.2005		Date of mailing of the international search report 22.11.2005
Name and mailing address of the ISA/JP <b>Japan Patent Office</b> 3-4-3, Kasumigaseki, Chiyoda-ku, Tokyo 100-8915, Japan		Authorized officer <b>Shuichiro Ako</b> Telephone No. +81-3-3581-1101 Ext. 3546